

HOSE REELS

For Vehicle Exhaust



Diesel Fumes

*Carbon Monoxide
Fumes*

*Car & Truck
Dealerships*

*Vehicle Repair
Facilities*

meets OSHA air quality standards



Springloaded or Motorized

*Hose Capacity on Reel:
Diameter: 4", 5", 6"
Lengths: 25', 33', 42'
Maximum Temperature:
up to 2000° F*



OsKar Exhaust Hose Reel

OSKAR Exhaust Hose Reels are designed for the extraction of car and truck gases at the tail pipe which are emitted inside buildings. They are designed for facilities such as vehicle service garages and vehicle storage garages as well as hard to reach areas for many other types of fumes and gases. A flexible hose mounted on the reel allows for extraction of gas-air mixture with maximum temperature 2000° F (1150° C) Hoses of 4" to 6" and lengths up to 42' simplify the servicing of vehicles. Flexible hose may be fitted with a variety of tail pipe nozzles depending on the vehicle being serviced. The outlet of the hose reel is designed to connect to 6" diameter ducting.



User Friendly features include:

- Motorized or manual rolling and unrolling
- Made from heavy gauge welded steel
- Maximum temperature of 2000° F (1150° C)
- Designed for "hard to reach areas"
- Each reel is fully adjustable in tension to give required retraction.
- Flexible hose can be fitted with a variety of tail pipe nozzles
- Ratchet locking system to lock hose in place



Hose reel can be mounted in any position as long as the drum is in the horizontal position. Minimum mounting height is 8 ft. [2.5 M].



A fan may be mounted directly to the reel.



Other OsKar Air Products Equipment



Booms



Arms



Portable



Modular Filters

Exhaust Rails



North American Distributor of Oskar Air Products:
 Industrial Air Quality, Inc
 102 AG Drive
 Youngsville, NC 27596
 ph: 919 562-7181 fx: 919 562-7182

Model No.	Diameter of hose [in.]	Max. length of hose [ft]	Width of drum (in.)	Net weight (lbs.)**
8710010	4"	up to 33'	29"	128
M 8710010*	4"	up to 33'	29"	93
8712510	5"	up to 33'	34"	132
M 8712510*	5"	up to 33'	34"	97
8715010	6"	up to 33'	38"	137
M 8715010*	6"	up to 33'	38"	102

* Motorized remote control hose reel

** Weight does not include flexible hose.

Lengths may be increased by allowing more hose to hang from reel drum. Call for pricing on hoses and nozzles.

Recommended Temperatures:

- standard flexible hose: 350° F
- standard diesel: 570° F
- high temperature: 1000° F - 2000° F

Remote control on new motorized hose reels

Oskar electric motor-driven hose reels are designed to handle both large and small diameter hoses.

Internal drum motor with programmable remote.

The motor-driven reel can recoil lengths of hose up to 55 ft. (17 M) of 6" (150mm) hose.

*Motor: Altus RTS - 50 NM of torque, amps 2.1, 120 volts, 240 watts, capable of lifting up to 440 lbs.

The OsKar motor-driven reel is designed to be either ceiling suspended or wall mounted.



Authorized Dealer or Distributor: